tem	Description				
	BASMENT PART	1			
	MASONRY WORK				
	200mm Thk. Walls in standard hollow concrete				
	block from an approved manufacturer in cement and				
	sand (1:3) mortar or as specified including filling				
	cavities with plain concrete, making solid at ends,				
	corners, jambs and sills				
A	Basement floor				
	HOTEL PART				
	MASONRY WORK				
	External walls				
*	Blockwork combination as per the drawings				
	200mm Thk. approved block work from an				
	approved manufacturer in cement and sand (1:3)				
	mortar or as specified including filling cavities with				
	plain concrete, making solid at ends, corners, jambs				
	and sills.				
A	To all floors				
	Internal walls				
	200mm Thk. Walls in standard hollow concrete				
	block from an approved manufacturer in cement and				
	sand (1:3) mortar or as specified including filling				
	cavities with plain concrete, making solid at ends,				
	corners, jambs and sills				
В	To all floors				
	APARTMENT AREA				
	MASONRY WORK				
	External walls				
*	Blockwork combination as per the drawings				
	200mm Thk. approved block work from an				
	approved manufacturer in cement and sand (1:3)				
	mortar or as specified including filling cavities with				
	plain concrete, making solid at ends, corners, jambs				
	and sills.				
A	To all floors				
	Internal walls				
	200mm Thk. Walls in standard hollow concrete				
	block from an approved manufacturer in cement and				
	sand (1:3) mortar or as specified including filling				
	cavities with plain concrete, making solid at ends,				
	corners, jambs and sills				
В	To all floors				
	MASONRY WORK (cont'd)				
	Parapet walls				
	Walls in hollow block work filled with concrete				
	with steel T12 @ 400 centers, in parapets built in				
	cement and sand (1:3) mortar or as specified				
A	200mm Thick block work				
	II	1	1	1	1